

DRY BAG PS 490

Durable dry bag with roll closure



Reliable roll closure with single reinforcement strip
Side-release buckles and D-rings for safeguarding



Carrying handle (only 59 to 109 L versions)



Indication of volume in liters



Recommendation by German motorcycle magazine Motorrad ABENTEUER (59L version), May/June 2012



Valve for deflation

Version black-lemon with valve for deflation



Bottom loop for anchoring and holding

Size/L	Height cm/in.	Circ. cm/in.	Diam. cm/in.	Volume l/cu.in.	Weight g/oz.
13 L	42/16.5	60/23.6	19/7.5	13/793	290/10.2
22 L	52/20.5	70/27.6	22/8.7	22/1343	370/13.0
35 L	60/23.6	83/32.7	26/10.2	35/2136	450/15.9
59 L	70/27.6	96/37.8	31/12.2	59/3600	640/22.6
79 L	75/29.5	107/42.1	34/13.4	79/4821	750/26.5
109 L	80/31.5	122/48	39/15.4	109/6652	900/31.7

= height valid for closed bag (rolled 3x); add about 20 cm/ 8 in. for open bag;

- Sturdy heavy duty dry bag for extreme conditions
- Version black-lemon with valve for deflation and inflation
- Strong robust coated fabric with excellent increased tear-resistance
- Loop at the bottom for anchoring or holding (when pulling contents out of the bag)
- Sizes 59 to 109 L come with carrying handle
- With two D-rings for safeguarding
- Bottom made of PD 620 (higher stability when putting down)
- Suitable for caving or other heavy duty purposes
- Easy to clean inside

Note: In order to meet standard IP64 (6=dustproof, 4=protected against splash water coming from all directions) the roll closure must be rolled at least 3-4 times.

PRODUCT-INFO

Please find information on IP symbols on our info sheet or at www.ortlieb.com/ip-symbols

ps490-02_2014