ORTLIEB (WATERPROOF)

BIKE-PACKER CLASSIC

Rear pannier pair with lid and QL2.1 system







at www.ortlieb.com/ip-symbols

sheet or

Please find information on IP symbols on our info









Carrying handle for mounting and releasing – the QL2.1 system

Automatically closing 16mm QL2.1 hooks

Exchangeable hook inserts with antiscratch function (8, 10, 12 mm)

Adjustable and rotatable mounting hook (in 15° steps) with anti-scratch function

Semi-elliptical hook rail made of two-component synthetic with anti-scratch function reduces abrasions on rack

Edge protector with slots for mounting the ORTLIEB carrying system

Height cm/in	Width cm/in	Depth cm/in	Volume L/cu.in.	Weight g/oz.
42/16.5	23/32 9/12.6	17/6.7	40/2441 (pair)	2080/73.4 (pair)

SPECIFICATIONS:

- + Panniers (pair) with classic lid closure for large packing volume
- + Sides of PS 490 nylon material, front and back of PD 620
- + QL2.1 mounting system for racks with max. 16 mm tube diameter
- + 20 mm hook available as separate accessory (e.g. for E-bikes)
- + Reduction inserts for tube diameters 8, 10 und 12 mm with anti-scratch function preventing abrasion on the rack
- + Hooks adjustable without requiring tools
- + Lower hook rail made of two-component hard-soft synthetic with anti-scratch function protecting the rack
- + Including integrated inner pocket and shoulder strap
- + Due to its symmetrical form it is possible to use only one bag on left or right side
- + The dust flap with easily operable pull cord under the lid provides protection e.g. against water, dust and snow
- + The edge protector prevents contact with spokes and abrasion
- + Simultaneous use of ORTLIEB Travel-Biker possible
- + Highly reflective 3M Scotchlite reflector
- + Easy to clean inside

Contents: Panniers comes with shoulder strap, reduction inserts 8, 10 and 12 mm (2 pairs per size)

Optional accessories: ORTLIEB carrying system, outer pocket/s (size S), mesh pocket, bottle cage, 20 mm QL2.1 hook, anti-theft device long

Attention: Maximum load per bag or per side of carrier is 9 kg / 20 lbs. As the admissible load of carriers differ, note the maximum admissible load - (information is normally found on the carrier) - do not exceed the carrier load limit. We recommend to check-weigh packed bags before riding - reduce the load if necessary. This applies to rear and front carriers and also to lowriders mounted on the fork. Note that the use of bike panniers will significantly influence the riding properties of your bike.

Note: In order to meet standard IP54 (5=protected against dust, 4=protected against splash water coming from all directions) the lid must be properly closed.