



Max Suspension Spray

SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 1272/2008 (CLP)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

GHS Product Identifier	Not applicable.
Chemical Name	Not applicable.
Trade name	Max Suspension Spray
CAS No.	Mixture
EINECS No.	Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)	Lubricant
Uses advised against	None.

1.3 Details of the supplier of the safety data sheet

Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11788 USA
Telephone	+1 (631) 666-7300
Fax	+1 (631) 666-7391
E-Mail (competent person)	SDSinfo@finishlineusa.com
Distributor	Madison Cycles 8 Stanmore Hill Stanmore, Middlesex, HA7 3BQ United Kingdom
Telephone	+44 870 034 7226

1.4 Emergency telephone number

Emergency Phone No.	Medical Emergency: PROSAR 24 hr: 1-800-217-5157 / 1-651-523-0304
---------------------	---

Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP).

Flam. Aerosol 1; Asp. Tox. 1; Skin Irrit. 2; STOT SE 3; Aquatic Chronic 3

2.2 Label elements

Hazard Symbol



Danger

Signal word(s)

Hazard statement(s)

H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.



Max Suspension Spray

Precautionary statement(s)

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

P102: Keep out of reach of children.

2.3 Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Regulation (EC) No. 1272/2008 (CLP).

Hazardous ingredient(s)	%W/W	EC No. and CAS#	According to Regulation (EC) No. 1272/2008 (CLP)
Heptane, branched, cyclic and linear	50-70	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 3; H412
Propane	10-15	200-827-9 74-98-6	Flam. Gas 1, H220 Press. Gas (*)
Butane	5-10	203-448-7 106-97-8	Flam. Gas 1, H220 Press. Gas (*)

For full text of H/P phrases see section 16.

SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

Move person to fresh air. If breathing is laboured, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms occur obtain medical attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment.

4.2 Most important symptoms and effects, both acute and delayed

Will cause skin irritation.
Vapours may cause drowsiness and dizziness.

4.3 Indication of the immediate medical attention and special treatment needed

None

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media



Max Suspension Spray

- Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or waterspray.
- Unsuitable Extinguishing Media Do not use water jet.
- 5.2 Special hazards arising from the substance or mixture** Highly flammable vapour (flash point below 23°C).
- 5.3 Advice for fire-fighters** A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.
- 6.2 Environmental precautions** Prevent substance entering sewers.
- 6.3 Methods and material for containment and cleaning up** Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
- 6.4 Reference to other sections** None

SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.
- 7.2 Conditions for safe storage, including any incompatibilities**
 - Storage Temperature Keep container in a well-ventilated place. Store at temperatures not exceeding 38°C/100°F.
 - Incompatible materials None
- 7.3 Specific end use(s)** Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
- 8.1.1 Occupational Exposure Limits**

SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note:
Heptane, branched, cyclic and linear	426260-76-6	-----	1800	-----	-----	UK - EH40
n-Heptane	142-82-5	500	2085	-----	-----	EU - IOEL
n-Butane	105-97-8	600	1450	750	1810	UK - EH40

Biological limit value

Limit value type (country of origin)	SUBSTANCE.	CAS No.	Biological limit value	Note:
None known	None	-----	None	None

- 8.1.2 Recommended monitoring method** UK HSE Method 96 (n-Heptanel)
- 8.2 Exposure controls**
- 8.2.1 Appropriate engineering controls** Use only with adequate ventilation to keep exposures (airborne levels of dust, fume, vapour etc) below recommended exposure limits.
- 8.2.2 Personal protection equipment**



Max Suspension Spray

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber)

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required.

8.2.3 Environmental Exposure Controls

None assigned.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Petroleum spirit
Odour Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive limit ranges	2.1% - 9.5% v/v (Propane)
Vapour Pressure (Pascal)	ca. 95×10^4 (Propane)
Vapour Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Temperature (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cP @ 40°C)	<20.5
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

Not available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable.
10.3 Possibility of hazardous reactions	None anticipated.
10.4 Conditions to avoid	Avoid contact with heat and ignition sources.
10.5 Incompatible materials	Strong Acids.
10.6 Hazardous Decomposition Product(s)	None known

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

11.1.1 Substances



Max Suspension Spray

Not applicable

11.1.2 Mixtures

Acute toxicity	Not available
Skin corrosion/irritation	Not available
Serious eye damage/irritation	Not available
Respiratory or skin sensitization	Not available
Germ cell mutagenicity	Not available
Carcinogenicity	Not available
Reproductive toxicity	Not available
STOT - single exposure	Not available
STOT - repeated exposure	Not available
Aspiration hazard	Not available

11.1.3 Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat
Skin corrosion/irritation	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	May cause eye irritation.
Respiratory or skin sensitization	It is not a skin sensitiser.
Germ cell mutagenicity	Not to be expected.
Carcinogenicity	Not to be expected.
Reproductive toxicity	Not to be expected.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	Not to be expected. - NOAEC: 12350 mg/m ³ (2 yr, inhal., rat, Systemic effects) - LOAEC: 1650 mg/m ³ (2 hr, inhal., rat, CNS effects)
Aspiration hazard	Aspiration of droplets may cause pulmonary oedema.

Propane (CAS# 74-98-6):

Acute toxicity	Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)
Skin corrosion/irritation	Not to be expected.
Serious eye damage/irritation	Not to be expected.
Respiratory or skin sensitization	It is not a skin sensitiser.
Germ cell mutagenicity	Not to be expected.
Carcinogenicity	Not to be expected.
Reproductive toxicity	Not to be expected.
STOT - single exposure	Not to be expected.
STOT - repeated exposure	Not to be expected. - NOAEC: ≥19678 mg/m ³ (28-day, rat, Systemic effects) - LOAEC: 21641 mg/m ³ (28-day, rat, effects: Body weight)
Aspiration hazard	Aspiration of droplets may cause pulmonary oedema.

11.2 Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

12.1.1 Substances in preparations / mixtures

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 3 mg/l (<i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Long Term	LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>)

12.2 Persistence and degradability

Readily biodegradable.

12.3 Bioaccumulative potential

The product has low potential for bioaccumulation.

12.4 Mobility in soil

The product is predicted to have high mobility in soil.



Max Suspension Spray

12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
------	-------------------------	--

SECTION 14: TRANSPORT INFORMATION

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO/IATA)
14.1	UN number	1950	1950
14.2	Proper Shipping Name	Aerosols	Aerosols
14.3	Transport hazard class(es)	2.1	2.1
14.4	Packing Group	Not applicable	Not applicable
14.5	Environmental hazards	None assigned	None assigned
14.6	Special precautions for user	None assigned	None assigned
14.7	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable		

SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture:	
15.1.1	EU regulations	Listed
	Regulation (EC) 2037/2000 - Dangerous to the ozone layer.	No.
	Regulation (EC) 850/2004 - Persistent Organic Pollutants	No.
	Regulation (EC) 689/2008 - Export/Import of Dangerous Chemicals	No.
	Regulation (EC) 1907/2006 - REACH Authorisations and/or restrictions on use	No.
15.1.2	National regulations	Not established.
15.2	Chemical Safety Assessment	Not applicable

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1 - 16.

Hazard statement(s) and Precautionary statement(s):

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapour.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H412: Harmful to aquatic life with long lasting effects.

GHS Classification

- Flam. Aerosol 1: Extremely flammable aerosol. Category 1
- Asp. Tox. 1: Aspiration hazard Category 1
- Skin Irrit. 2; Skin corrosion/irritation Category 2
- STOT SE 3; Specific target organ toxicity — single exposure Category 3
- Aquatic Chronic 3; Chronic aquatic toxicity, Category 3

Training advice: None.

Additional Information: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.