


Material Safety Data Sheet

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: C141 PTFE Lubricant
Other Name : -
Application and Character : Recommended for metals machine parts to lubricate to use
Manufacturer Name : Lifu Bicycle Co., Ltd. Address: No. 4, Lane 11, Ziqiang Street, Tucheng Dist., New Taipei City 23678, Taiwan Telephone Number: 886-2-22687367
Emergency Telephone Number/Fax Number: 886-2-22687367/ 886-2-22681947

II. HAZARDS IDENTIFICATION

NFPA Ratings (Scale 0-4):(NFPA FIRE=1)
Indication Con 
Other Harms : Does not have(NFPA FIRE=1)

III. COMPOSITION, INFORMATION ON INGREDIENT

1. Product Identification:		
Chemical Family: Polytetrafluoroethylene Dispersion		
Chemical Formula: Mixture		
Trade Name/Synonym: PTFE Dispersion in Mineral Oil		
2. Component:		
Ingredients	CAS Number	%by vol.
Petroleum Distillate	64741-88-4	5.0
Polytetrafluoroethylene	9002-84-0	5.0
Mineral Oil	64742-57-0	90.0

IV. FIRST AID MEASURE

Emergency Procedures:
<ul style="list-style-type: none">Inhalation : Remove personnel from exposure area to fresh air immediately. If breathing is difficult, give oxygen. If breathing ceases, use a oxygen rescuer or similar device to perform artificial respiration. Get medical attention immediately.Skin Contact :

Remove contaminated clothing, jewelry and shoes immediately. Wash with soap or mild detergent and large amounts of water until no evidence of chemical remains (at least 15~20 minutes). If irritation or adverse symptoms develop, seek medical attention.

• Eye Contact :

Flush eyes immediately with running water for at least fifteen minutes, occasionally lifting upper and lower lids, until no evidence of chemical remains. Get medical attention immediately.

• Digestion :

If swallowed, do not induce vomiting. If conscious, give 1~2 water to drink. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention immediately.

Protection of First-aiders: no information is available.

Notes to Physician: no information is available.

Notes to Doctor: no information is available.

V. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: regular dry chemical, carbon dioxide, water, regular Foam.

Large fires: Use regular foam or flood with fine water spray.

Specific Hazards: combustion conditions, oxides of the following elements will be formed:
carbon dioxide, water, sulfur, nitric oxide. Incomplete burning can produce carbon monoxide and other harmful products.

Special Fire Fighting Procedures:

1. Firefighters should wear proper protective equipment stay upwind.
2. Move container from fire area and shut off source if it can be done without risk.
3. Cool containers with water spray until well after the fire is out.
4. Do not scatter spilled material with high-pressure water streams.
5. Keep unnecessary people away, isolate hazard area and deny entry.
6. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions

1. Avoid heat, flames, sparks and other sources of ignition.
2. Stop leak if possible without personal risk.
3. Reduce vapors with water spray.

Environmental Precautions:

1. Eliminate all open flame in vicinity of spill or released vapor.

2. Stop the source of the leak or release.
3. Clean up releases as soon as possible.
4. Contain liquid to prevent further contamination of soil, surface water or groundwater.

Methods for Cleaning Up:

1. Clean up small spills using sand or other non-combustible material.
2. Collect spilled material in appropriate container for disposal.
3. Where feasible and appropriate, remove contaminated soil.
4. Follow prescribed procedures for reporting and responding to larger releases.

VII. HANDLING AND STORAGE

Handling:

1. Wear protective equipment, if exposure conditions warrant.
2. Wash thoroughly after handling.
3. Use with adequate ventilation.
4. Handle in accordance with all current regulations and standards.

Storage:

1. Keep away from heat, sparks and flames.
2. Store in well-ventilated area.
3. Store in a tightly closed container.
4. Store in a cool, dry place.
5. Bond and ground during transfer.
6. Keep separated from incompatible substances.
7. Storage in accordance with all current regulations and standards.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Control Parameter:

HAZARDOUS MATERIAL	TWA	STEL	CEILING
Mineral Oil Mist	ACGIH: 5 mg/m NIOSH: 5 mg/m ³ OSHA : 5 mg/m ³	NIOSH : 10mg/m UK OES : 10mg/m	---

Personal Protection Equipment:

- Respiratory Protection:
Not generally required unless needed to prevent respiratory irritation. In case of spill or leak resulting in unknown concentration, use NOISH approved supplied air respirator.
- Hand Protection:
Wear appropriate chemical resistant gloves.

- Eye Protection:
Wear splash resistant safety goggles or face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
- Skin and Body Protection:
Wear appropriate chemical resistant clothing. Remove any chemical soaked clothing immediately.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: liquid	Form: Light Brown liquid
Color: Light Brown	Odor: Oily
PH: Not available	Boiling Range: > 300°C
Decomposition Temperature: No data	Flash Point: > 200°C
Autoignition Temperature: No data	Test Method: Open Cup
Vapor Pressure: Not available	Flammable Limits: Not available
Solubility: insoluble in water	Vapor Density: Not available
Specific Gravity: 0.88-0.90g/cm ³ @ 60°F	

X. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure.
Possible Hazardous Reactions: Will not polymerize.
Conditions to Avoid: Avoid heat, flames, spark and other sources of ignition. Avoid contact with incompatible material.
Materials to Avoid: acid, strong oxidizing agents.
Hazardous Decomposition Products: oxides of carbon, various hydrocarbons and sulfide formed when burned.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

- **Inhalation:**
Mists or sprays of insoluble oils are not harmful to the respiratory tract, although worker discomfort may occur at oil mist level of 5 mg/m³.
- **Skin Contact:**
May cause hair follicles, comedones, perifollicular papules and pustules. Some individuals may develop a skin sensitivity to petroleum products.
- **Eye Contact:**
Found to be moderately irritating to rabbit eyes.
- **Ingestion:**
Mineral oils may cause gastrointestinal disturbance such as diarrhea.
- **Oxirane, Methyl-, Polymer with Oxirane:** LD50 500mg/Kg(Rat)

- **Local Effect:** No data available.
- **Sensitization:** No data available.

XII. ECOLOGICAL INFORMATION

Environmental Mobility: No data available.

XIII. DISPOSAL CONSIDERATIONS

Subject to disposal regulations:

Dispose in accordance with all applicable regulations.

XIV. TRANSPORT INFORMATION

IATA-DGR Class : UN Number-Not regulated

XV. REGULATORY INFORMATION

Suitable Regulations:

1. U.S. Regulations:

TSCA Inventory Status: Y

SARA Hazard Categories, SARA Sections 311/312(40 CFR 370.21):

Acute: N

Chronic: N

Fire: N

Reactive: N

OSHA Process Safety(29 CFR 1910.119): N

2. State Regulations:

California Proposition 65: N

3. European Regulations: EC Number: Not assigned

XVI. OTHER INFORMATION

Reference Literatures	1. OHS 15037 2. OHS 50243
Made By	Lifu Bicycle Co., Ltd.
	No. 4, Lane 11, Ziqiang Street, Tucheng Dist., New Taipei City 23678, Taiwan
	Title: G. Manager Signature : Alex Hsiao
Creation Date	June.25.2018