

Telefax: +49 (0) 941 70 46 60

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Innotech High - Tech Chain Fluid 105

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol - Lubricants, greases, release products

Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Company name: innotech-Vertriebs GmbH

Street: Junkerstrasse 16
Place: D-93055 Regensburg
Telephone: +49 (0) 941 70 08 78

e-mail: info@innotech-r.de

e-mail: info@innotech-r.de
Contact person: Mr. Massen
Internet: www.innotech-r.de
Responsible Department: sales department

1.4. Emergency telephone +49 (0) 941 70 08 78

number: Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 2 of 15

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to in accordance with local/regional/national/international

regulation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity				
	EC No	Index No	REACH No			
	GHS Classification	•	•			
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	918-481-9		01-2119457273-39			
	Asp. Tox. 1; H304 EUH066					
106-97-8	Butane			20 - < 25 %		
	203-448-7		01-2119474691-32			
	Flam. Gas 1, Liquefied gas; H220 H	H280				
74-98-6	Propane			10 - < 12.5 %		
	200-827-9		01-2119486944-21			
	Flam. Gas 1, Liquefied gas; H220 H					
	Hydrocarbons, C7-C9, n-alkanes, is	2.5 - < 5 %				
	920-750-0		01-2119473851-33			
	Flam. Liq. 2, STOT SE 3, Asp. Tox.					
68937-41-7	Phenol, isopropylated, phosphate (0.1 - < 0.5 %				
	273-066-3		01-2119535109-41			
	Repr. 2, STOT RE 2, Aquatic Chron					
61791-55-7	N-Tallow propylene diamine	0.1 - < 0.5 %				
	263-189-0		01-2119487014-41			
	Acute Tox. 4, Skin Corr. 1B, STOT H400 H411					
115-86-6	Triphenyl phosphate			0.1 - < 0.5 %		
	204-112-2		01-2119457432-41			
	Aquatic Chronic 1; H410					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 3 of 15

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 4 of 15

measures against static discharges. Vapours can form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Aerosol - Lubricants, greases, release products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
115-86-6	Triphenyl phosphate	-	3		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 5 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkane	s, cyclics		•
Worker DNEL	, long-term	dermal	systemic	773 mg/kg bw/day
Worker DNEL	, long-term	inhalation	systemic	2035 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	608 mg/m ³
Consumer DN	IEL, long-term	oral	systemic	699 mg/kg bw/day
68937-41-7	Phenol, isopropylated, phosphate (3:1)			
Worker DNEL	, long-term	inhalation	systemic	0,145 mg/m³
Worker DNEL	, acute	inhalation	systemic	700 mg/m³
Worker DNEL	, long-term	dermal	systemic	0,416 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	2000 mg/kg bw/day
Worker DNEL, acute		dermal	local	16 mg/cm²
Consumer DNEL, acute		inhalation	systemic	350 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	0,208 mg/kg bw/day
Consumer DN	IEL, acute	dermal	systemic	100 mg/kg bw/day
Consumer DN	IEL, acute	dermal	local	8 mg/cm ²
Consumer DN	IEL, long-term	oral	systemic	0,04 mg/kg bw/day
Consumer DN	IEL, acute	oral	systemic	50 mg/kg bw/day
115-86-6	Triphenyl phosphate			
Worker DNEL	, long-term	inhalation	systemic	5,2 mg/m³
Worker DNEL, long-term		dermal	systemic	5,55 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	0,9 mg/m³
Consumer DN	IEL, long-term	dermal	systemic	1,98 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	0,5 mg/kg bw/day



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 6 of 15

PNEC values

	-	
CAS No	Substance	
Environmenta	l compartment	Value
68937-41-7	Phenol, isopropylated, phosphate (3:1)	
Freshwater		0 mg/l
Freshwater (ir	ntermittent releases)	0,015 mg/l
Marine water		0 mg/l
Freshwater se	ediment	0,185 mg/kg
Marine sedime	ent	0,018 mg/kg
Secondary po	1,85 mg/kg	
Micro-organis	100 mg/l	
Soil	2,5 mg/kg	
115-86-6	Triphenyl phosphate	
Freshwater		0,004 mg/l
Freshwater (ir	ntermittent releases)	0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		1,103 mg/kg
Marine sedime	0,11 mg/kg	
Secondary po	16,667 mg/kg	
Micro-organis	5 mg/l	
Soil		0,218 mg/kg

8.2. Exposure controls

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection DIN EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber) EN ISO 374

Thickness of the glove material: >=0,4mm.

Breakthrough time (maximum wearing time): 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus: Combination filtering device (EN 14387) AX-P2



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 7 of 15

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: light yellow

Odour: like: lubricant, gun-oil and gun-cleaner, rust protection

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:
Initial boiling point and boiling range:

<-20 °C

Flash point:

<-20 °C

Sustaining combustion:

No data available

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

Heating may cause an explosion. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 15 vol. %
Ignition temperature: > 200 °C

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,685 g/cm³ calculated.

Water solubility: practically insoluble

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient:

Viscosity / dynamic:

Vapour density:

Evaporation rate:

not determined
not determined
not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 8 of 15

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Hydrocarbons, C10-C13,	n-alkanes, is	oalkanes, c	yclics, < 2% aromatics	•	
	oral	LD50 mg/kg	> 5000	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1989)	OECD Guideline 402
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat	OECD 403	
	Hydrocarbons, C7-C9, n-	alkanes, isoa	lkanes, cycl	lics		
	oral	LD50 mg/kg	>5000	Rat		
	dermal	LD50 3100 mg/kg	> 2800 -	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50	16 mg/l	Rat	Toxicology and Applied Pharmacology 32:	OECD Guideline 403
68937-41-7	Phenol, isopropylated, ph	osphate (3:1))			
	dermal	LD50 mg/kg	> 10000	Rabbit	Study report (1976)	other: 16 CFR 1500. 40
61791-55-7	N-Tallow propylene diami	ne				
	oral	ATE mg/kg	500			
115-86-6	Triphenyl phosphate					
	oral	LD50 mg/kg	> 20000	Rat	Study report (1976)	OECD Guideline 401
	dermal	LD50 mg/kg	> 10000	Rabbit	Study report (1976)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 9 of 15

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 10 of 15

CAS No	Chemical name									
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method			
	Hydrocarbons, C10-C13,	n-alkanes,	soalkanes, cy	/clics, <	2% aromatics					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	OECD Guideline 203				
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	OECD Guideline 202				
	Fish toxicity	NOEC mg/l	0,101	28 d	Oncorhynchus mykiss	REACh Registration Dossier	The aquatic toxicity was estimated by a			
	Crustacea toxicity	NOEC mg/l	0,176	21 d	Daphnia magna	REACh Registration Dossier	The aquatic toxicity was estimated by a			
06-97-8	Butane									
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo			
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.			
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.			
74-98-6	Propane									
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo			
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.			
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.			
	Hydrocarbons, C7-C9, n-a	alkanes, iso	alkanes, cycli	cs						
	Acute fish toxicity	LC50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	OECD Guideline 203				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Raphidocelis subcapitata	OECD Guideline 201				
	Acute crustacea toxicity	EC50	7,4 mg/l	48 h	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 202			
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS	The aquatic toxicity was estimated by a			
	Algea toxicity	NOEC	(10) mg/l	3 d	Pseudokirchneriella subcapitata					
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211			



according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 11 of 15

	Acute fish toxicity	LC50 mg/l	10,8	96 h	Pimephales promelas	REACh Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 2,5	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50	1,5 mg/l	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,0031	33 d	Pimephales promelas	REACh Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,0415	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(> 1000	mg/l)	3 h	activated sludge, domestic	REACh Registration Dossier	OECD Guideline 209
115-86-6	Triphenyl phosphate						
	Acute fish toxicity	LC50	0,4 mg/l	96 h	Oncorhynchus mykiss	REACh Registration Dossier	other: see below
	Acute algae toxicity	ErC50 mg/l	2,45	72 h	Pseudokirchneriella subcapitata	Study report (2000)	OECD Guideline 201
	Acute crustacea toxicity	EC50	1 mg/l	48 h	Daphnia magna	Aquatic Toxicology and Hazard Assessment	other: see below
	Fish toxicity	NOEC mg/l	>= 0,001	90 d	Oncorhynchus mykiss	Aquatic Toxicology and Hazard Assessment	Flow through system with 90d exposure pe
	Crustacea toxicity	NOEC mg/l	0,254	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics						
	Biodegradation	80%	28				
	Readily biodegradable (according to OECD criteria).						
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D			
	Readily biodegradable (according to OECD criteria).	-					

12.3. Bioaccumulative potential

The product has not been tested.



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

	Innotech High - Tech Chain Fluid 105	
Revision date: 29.11.2019		Page 12 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	Butane	1,09
74-98-6	Propane	1,09
68937-41-7	Phenol, isopropylated, phosphate (3:1)	85000 - 150000
115-86-6	Triphenyl phosphate	4,63

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	144,3	calculated	Other company data (
68937-41-7	Phenol, isopropylated, phosphate (3:1)	225	Lepomis macrochirus	REACh Registration D
115-86-6	Triphenyl phosphate	144	Oryzias latipes	REACh Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code:

Special Provisions:

190 327 344 625



according to Regulation (EC) No 1907/2006

	Innotech High - Tech Chain Fluid 105	
Revision date: 29.11.2019		Page 13 of 15

Limited quantity:1 LExcepted quantity:E0Transport category:2Tunnel restriction code:D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 14 of 15

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 88,341 % (605,135 g/l) 2004/42/EC (VOC): 88,347 % (605,177 g/l)

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration



Print date: 29.11.2019

according to Regulation (EC) No 1907/2006

Innotech High - Tech Chain Fluid 105

Revision date: 29.11.2019 Page 15 of 15

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

EmS: Emergency Schedules MFAG: Medical First Aid Guide

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

iovant ir and Eori statements (namber and rail text)	
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)