MOTIP DUPLI

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

	ation of the substance/mixture and of the company/undertaking
• 1.1 Product identifier • Trade name: <u>MOTIP CYC</u>	LING SUPER LUBRICANT 400 ml / 200 ml
• Article number: 000273 / • 1.2 Relevant identified uses No further relevant informa • Application of the substance	s of the substance or mixture and uses advised against tion available.
• 1.3 Details of the supplier of Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.	
	nable from: QHSE Department number: +31 (0)561-694400 (09:00h - 17:00h)
SECTION 2: Hazards	identification
GHS02 flame	
Flam. Aerosol 1 H222-H	
Flam. Aerosol 1 H222-H	ent
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411	ent
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411	ent Toxic to aquatic life with long lasting effects.
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC able
Flam. Aerosol 1 H222-F GHS09 environm Aquatic Chronic 2 H411 6 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to F+; Extremely flamm	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC able nable.
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to F+; Extremely flamm R12: Extremely flamm N; Dangerous for the	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC able nable.
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 6 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to F+; Extremely flamm R12: Extremely flamm R12: Extremely flamm R12: $R12$: $R12$	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC able nable. environment
Flam. Aerosol 1 H222-H GHS09 environm Aquatic Chronic 2 H411 4 GHS07 Skin Irrit. 2 H315 STOT SE 3 H336 Classification according to F+; Extremely flamm R12: Ext	ent Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. Directive 67/548/EEC or Directive 1999/45/EC able nable. environment organisms, may cause long-term adverse effects in the aquatic environment. ure may cause skin dryness or cracking. Vapours may cause drowsiness and pricular hazards for human and environment: led due to the calculation procedure of the "General Classification guideline fo

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

ade name: M	10TIP CYCLING SU	IPER LUBRICANT 400 ml / 200 ml
		(Contd. of p
Warning! I	Pressurised container.	
	cotising effect.	
· Classificat	ion system:	
The classif	ication is according to	the latest editions of the EU-lists, and extended by company and literate
data.		
· 2.2 Label e	elements	
· Labelling (according to Regulati	ion (EC) No 1272/2008
		elled according to the CLP regulation.
• Hazard pic	ctograms	
\wedge	\wedge	
Atte S		
	\times	
GHS02	GHS07 GHS09	
011002	011007	
· Signal wor	d Danger	
	termining component	ts of labelling.
pentane	and and a component	o oj moening.
1	petroleum), hydrotreat	ted light
· Hazard sta		
		e aerosol. Pressurised container: May burst if heated.
H315	Causes skin irritatio	n.
H336	May cause drowsine	ess or dizziness.
H411	Toxic to aquatic life	with long lasting effects.
	ary statements	
P102	Keep out of reach o	
P260	Do not breathe spra	
P210		at, hot surfaces, sparks, open flames and other ignition sources. No smok
P251	Do not pierce or bu	
P211		open flame or other ignition source.
P501		ht. Do not expose to temperatures exceeding 50 °C/122 °F. /container in accordance with local regulations.
	information:	container in accordance with local regulations.
		v cause skin dryness or cracking.
· 2.3 Other 1		cause skin aryness of cracking.
	PBT and vPvB assess	sment
• PBT: Not a		
• vPvB: Not		
SECTIO	N 3: Composition	/information on ingredients
· 3.2 Chomi	cal characterisation:	Mixtures
		ces listed below with nonhazardous additions.
•	s components:	
CAS: 109-0	-	pentane 25-5
EINECS: 2		∑23-5 X <i>N</i> R65
	ber: 601-006-00-1	F + R12
	-2119459286-30-xxx	
neg ni (ii	0,0,200 00 mm	R66-67
reg.m 01		
reg.nr 01		
Keg.nr., 01		(A) ASD. 10X. 1, H304
Neg.nr 01		Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Keg.nr., 01		Asp. 10x. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

		(Contd. of page 2
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane F + R12 Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Naphtha (petroleum), hydrotreated light Xn R65 Xi R38 F R11 N R51/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	12.5-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F + R12 Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F + R12 Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%
	Mineral oil 🚯 Asp. Tox. 1, H304	5-10%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• *After swallowing:* Drink plenty of water and provide fresh air. Call for a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• For safety reasons unsuitable extinguishing agents: Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

Keep away from ignition sources.

- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

• Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

• Respiratory protection: Not required.

• Protection of hands: Not required.

· Material of gloves Not required.

· Penetration time of glove material Not required.

• Eye protection: Not required.

(Contd. on page 5)

(Contd. of page 3)

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

(Contd. of page 4)

9.1 Information on basic physical an	d chemical properties
General Information	
Appearance:	
Form:	Aerosol
Colour: Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
•	
Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
	**
Flash point:	< 0 °C (< 32 °F) Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C (> 392 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	0.625 g/cm ³ (5.216 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	90.0 %
EU-VOC:	562.5 g/l
EU-VOC in %:	90.00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

e 6) - GB

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. of page 5)

SECTION 11: Toxicological information

-11.1 Information on toxicological effects

· Acute toxicity · I.D/I.C50 values relevant for classification.

109-66-0 pentane		
Dermal	LD50	>2500 mg/kg (rat)
		>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>100 mg/m3 (rat)
64742-49-0	0 Naphtha (p	etroleum), hydrotreated ligh
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>193 mg/m3 (rat)
	LC50 / 4h	25.2 mg/l (rat)
	LC50 / 96 h	11.4 mg/l (fish)
106-97-8 b	outane	

Inhalative LC50 / 4 h 658000 mg/m3 (rat)

Primary irritant effect:

· Skin corrosion/irritation No irritant effect.

- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

LC50 / 96 h 1-10 mg/l (fish)

64742-49-0 Naphtha (petroleum), hydrotreated light

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h 30-100 mg/l (algae)

LC50 / 96 h 93-117 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark: Toxic for fish
- Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

(Contd. on page 7)

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

(Contd. of page 6)

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Product contains environmentally hazardous substances: pentane
Marine pollutant:	No Warding Course
116 Chapiel nucleastices for second	
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Gases. - F-D,S-U
Danger code (Kemler):	- F-D,S-U
Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Anne	F-D,S-U ex II of
Danger code (Kemler): EMS Number: 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	F-D,S-U ex II of

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

	(Contd. of page 7)
• Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
• UN "Model Regulation":	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

• Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- *R65 Harmful: may cause lung damage if swallowed.*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67* Vapours may cause drowsiness and dizziness.

Department issuing MSDS: R&D legislation and regulatory advisor

- Contact: Mr. K. Smedeman
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Gas 1: Flammable gases, Hazara Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

(Contd. on page 9)

Printing date 02.06.2015

Version number 18

Revision: 02.06.2015

Trade name: MOTIP CYCLING SUPER LUBRICANT 400 ml / 200 ml

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 · * **Data compared to the previous version altered.**

(Contd. of page 8)

GB