

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

\*

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml
- **Article number:** 000284 / 000295
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Lubricant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MOTIP DUPLI B.V.  
Wolfraamweg 2  
NL- 8471 XC Wolvega  
The Netherlands  
Tel: +31 (0)561 694400  
Fax: +31 (0)561 694411  
e-mail [info@nl.motipdupli.com](mailto:info@nl.motipdupli.com)
- **Further information obtainable from:** QHSE Department
- **1.4 Emergency telephone number:** +31 (0)561-694400 (09:00h - 17:00h)

\*

#### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Extremely flammable

R12: Extremely flammable.

R52/53-66: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

**Trade name: MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 1)

**Hazard pictograms**

GHS02

**Signal word** Danger**Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

\*

**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

	Mineral oil ⚠ Asp. Tox. 1, H304	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ F+ R12 ⚠ Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
CAS: 64742-48-9 EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Naphta (petroleum), hydrotreated heavy ⚠ Xn R65 R66-67 ⚠ Asp. Tox. 1, H304	10-12.5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ F+ R12 ⚠ Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%

(Contd. on page 3)

GB

## Safety data sheet










### according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

**Trade name: MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 2)		
CAS: 109-66-0 EINECS: 203-692-4 Index number: 601-006-00-1 Reg.nr.: 01-2119459286-30-xxxx	pentane  Xn R65  F+ R12  N R51/53 R66-67 -----  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336	10-12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane  F+ R12 -----  Flam. Gas 1, H220 Press. Gas C, H280	10-12.5%
· <b>Additional information:</b> For the wording of the listed risk phrases refer to section 16.		

\*

#### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

\*

#### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

\*

#### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

GB

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

Trade name: **MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 3)

\*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

\*

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### 106-97-8 butane

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

##### 109-66-0 pentane

WEL	Long-term value: 1800 mg/m <sup>3</sup> , 600 ppm
-----	---

- **Additional information:** The lists valid during the making were used as basis.

#### 8.2 Exposure controls

- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:** Not required.
- **Protection of hands:** Not required.
- **Material of gloves:** Not required.
- **Penetration time of glove material:** Not required.
- **Eye protection:** Not required.

\*

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

#### General Information

##### Appearance:

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

Trade name: **MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 4)

· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Not applicable, as aerosol.
· <b>Flash point:</b>	< 0 °C (< 32 °F) Not applicable, as aerosol.
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	> 200 °C (> 392 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	10.9 Vol %
· <b>Vapour pressure at 20 °C (68 °F):</b>	3500 hPa (2625 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.675 g/cm <sup>3</sup> (5.633 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	65.0 %
· <b>EU-VOC:</b>	438.8 g/l
· <b>EU-VOC in %:</b>	65.00 %
· <b>Solids content:</b>	34.0 %
· <b>9.2 Other information</b>	No further relevant information available.

\*

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

Trade name: **MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 5)

\*

### SECTION 11: Toxicological information

#### · 11.1 Information on toxicological effects

##### · Acute toxicity

##### · LD/LC50 values relevant for classification:

##### 64742-48-9 Naphta (petroleum), hydrotreated heavy

Oral LD50 &gt;15000 mg/kg (rat)

Dermal LD50 &gt;3000 mg/kg (rab)

Inhalative LC50 / 4 h &gt;2.8 mg/m3 (rat)

##### 106-97-8 butane

Inhalative LC50 / 4 h 658000 mg/m3 (rat)

##### 109-66-0 pentane

Oral LD50 &gt;16000 mg/kg (rat)

Dermal LD50 &gt;2500 mg/kg (rat)

&gt;5000 mg/kg (rabbit)

Inhalative LC50 / 4 h &gt;100 mg/m3 (rat)

##### · Primary irritant effect:

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

\*

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 64742-48-9 Naphta (petroleum), hydrotreated heavy

LC50 / 96 h &gt;100 mg/l (crustacean (amphipod))

&gt;100 mg/l (fish)

##### 109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

LC50 / 96 h 1-10 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

##### · Ecotoxicological effects:

· Remark: Harmful to fish

##### · Additional ecological information:

##### · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

##### · 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

GB

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

Trade name: MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml

(Contd. of page 6)

\*

**SECTION 13: Disposal considerations**

## · 13.1 Waste treatment methods

## · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

## · European waste catalogue

20 01 13*	solvents
15 01 04	metallic packaging

## · Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

\*

**SECTION 14: Transport information**

## · 14.1 UN-Number

## · ADR, IMDG, IATA

UN1950

## · 14.2 UN proper shipping name

## · ADR

1950 AEROSOLS

## · IMDG

AEROSOLS

## · IATA

AEROSOLS, flammable

## · 14.3 Transport hazard class(es)

## · ADR



## · Class

2 5F Gases.

## · Label

2.1

## · IMDG, IATA



## · Class

2.1

## · Label

2.1

## · 14.4 Packing group

## · ADR, IMDG, IATA

Void

## · 14.5 Environmental hazards:

## · Marine pollutant:

No

## · 14.6 Special precautions for user

Warning: Gases.

## · Danger code (Kemler):

-

## · EMS Number:

F-D, S-U

## · 14.7 Transport in bulk according to Annex II of

## MARPOL 73/78 and the IBC Code

Not applicable.

## · Transport/Additional information:

## · ADR

## · Limited quantities (LQ)

1L

## · Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

## · Transport category

2

(Contd. on page 8)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 155

Revision: 02.06.2015

**Trade name: MOTIP CYCLING PTFE SPRAY 400 ml / 200 ml**

(Contd. of page 7)

· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	IL
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
  - H220 Extremely flammable gas.
  - H225 Highly flammable liquid and vapour.
  - H280 Contains gas under pressure; may explode if heated.
  - H304 May be fatal if swallowed and enters airways.
  - H336 May cause drowsiness or dizziness.
  - H411 Toxic to aquatic life with long lasting effects.
- R12 Extremely flammable.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- **Department issuing MSDS:** R&D legislation and regulatory advisor
- **Contact:** Mr. K. Smedeman
- **Abbreviations and acronyms:**
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - Flam. Gas 1: Flammable gases, Hazard Category 1
  - Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
  - Press. Gas C: Gases under pressure: Compressed gas
  - Flam. Liq. 2: Flammable liquids, Hazard Category 2
  - STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
  - Asp. Tox. 1: Aspiration hazard, Hazard Category 1
  - Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
  - Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3
- **\* Data compared to the previous version altered.**

GB