

Version number 4.0

Revision: 04.04.2019

1 Identification

- · Product identifier
- Trade name: <u>COPPER SPRAY</u>
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture** Lubrication, anticorrosive Only for proper handling.
- \cdot Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse 31 CH–4901 Langenthal Telefon +41 (0)62 919 75 75

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD Australia Phone : 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222 Extremely flammable aerosol.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Danger

 Hazard-determining components of labelling: Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

isopentane

Hazard statements

H222 Extremely flammable aerosol.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.

(Contd. on page 2)

[·] AU

Safety Data Sheet

according to WHS Regulations Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

Printing date 04.04.2019

	(Contd. of page 1)
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P301+P31	10 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P304+P34	40 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P403+P23	33 Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P41	12 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other haz	zards
Results o	f PBT and vPvB assessment

· **PBT:** Not applicable.

• vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1, H220; Press. Gas C, H280	50-70%
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT SE 3, H336	≥10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1, H220; Press. Gas C, H280	10-25%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8	isobutane Flam. Gas 1, H220; Press. Gas C, H280	1-2.5%
· Regulation (EC) No 648/200	04 on detergents / Labelling for contents	
aliphatic hydrocarbons	2	≥15 - <30%
• Additional information: For	the wording of the listed hazard phrases refer to section 1	6.

4 First Aid Measures

· Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

AU

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

(Contd. of page 2)

5 Fire Fighting Measures

Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

NES Long-term value: 1900 mg/m³, 800 ppm

WES Long-term value: 1900 mg/m³, 800 ppm

74-98-6 propane

NES Asphyxiant

(Contd. on page 4)

AU

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

DNELs	hyxiant		
Hydrocarl	oons, C7-C9, n-alkar	nes, isoalkanes, cyclics	
Oral	DNEL/general popula	ation/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Sy	stemic effects / Long-term	773 mg/kg/24h (worker)
	•	•	699 mg/kg/24h (consumer)
Inhalative		/stemic effects / Long-term	2,035 mg/m3 (worker)
	•	ation/Systemic effects/Long-term	
Additiona		sts valid during the making were u	,
Exposure		5 5	
	protective equipmer	nt:	
	rotective and hygie		
Keep away	/ from foodstuffs, bev	rerages and feed.	
	ds before breaks and		
	ale gases / fumes / a	erosols.	
	ry protection: brief exposure or low	v pollution use respiratory filter de	avice. In case of intensive or long
		spiratory protective device.	wice. In case of intensive of long
	sary if room is well-ve		
Respirator	y protection if formati	ion of aerosol or mist: use mask w	ith filter type A2, A2/P2 or ABEK.
	n of hands:		
		e impermeable and resistant to	the product/ the substance/ t
preparation		on consideration of the nonstrati	on times rates of diffusion and t
degradatic		on consideration of the penetration	on times, rates of diffusion and t
Material o			
		sistant to oil in use. Standard EN 3	874 Level 3 control G1
		oves does not only depend on the	
		facturer to manufacturer.	
	on rubber (Viton)		
Nitrile rubb		motorial: 0.4 mm	
Recomme		e material: \geq 0.4 mm	
		torial	
Penetratio	on time of glove mat		acturer of the protective gloves a
Penetratio	on time of glove mat break through time h	terial has to be found out by the manufa	acturer of the protective gloves a
Penetratio The exact has to be of For the mil	on time of glove mat break through time h bbserved. ixture of chemicals n	has to be found out by the manufa nentioned below the penetration	
Penetratio The exact has to be o For the mil (Permeation	on time of glove mat break through time h bbserved. ixture of chemicals n on according to EN 37	has to be found out by the manufa nentioned below the penetration	
Penetratic The exact has to be o For the mi (Permeatic Eye prote	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required.	has to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1).	
Penetratic The exact has to be o For the mi (Permeatic Eye prote	on time of glove mat break through time h bbserved. ixture of chemicals n on according to EN 37	has to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1).	
Penetratic The exact has to be o For the mi (Permeatic Eye prote	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required.	has to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1).	
Penetratio The exact has to be o For the mi (Permeation Eye prote Body prote	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required.	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing	
Penetratio The exact has to be o For the mi (Permeatio Eye prote Body prote Physica	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. tection: Protective wo l and Chemical F	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing P roperties	
Penetratio The exact has to be o For the min (Permeation Eye prote Body prote Body prote Physical Information	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. tection: Protective wo and Chemical F on on basic physical	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing	
Penetratio The exact has to be o For the mi (Permeatio Eye prote Body prote Body prote Physica Informatio General In	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required. tection: Protective wo l and Chemical F on on basic physical formation	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing P roperties	
Penetratio The exact has to be of For the min (Permeation Eye prote Body prote Body prote Physica Information General In	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required. tection: Protective wo l and Chemical F on on basic physical formation	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing P roperties	
Penetratio The exact has to be o For the mi (Permeatio Eye prote Body prote Body prote Body prote Body prote Informatio General In Appearan	on time of glove mat break through time h observed. ixture of chemicals n on according to EN 37 ction: Not required. tection: Protective wo l and Chemical F on on basic physical formation	nas to be found out by the manufa mentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured	
Penetratic The exact has to be of For the mil (Permeation Eye prote Body Body Body Body Body Body Body Body Body	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. fection: Protective wo l and Chemical F on on basic physical of ormation ce:	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured Solvent-like	
Penetratio The exact has to be o For the mi (Permeatio Eye prote Body Prote B	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. fection: Protective wo l and Chemical F on on basic physical of ormation ce:	nas to be found out by the manufa mentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured	
Penetratic The exact has to be of For the mil (Permeation Eye prote Body Body Body Body Body Body Body Body Body Body Body Body Body Body	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. fection: Protective wo l and Chemical F on on basic physical of ormation ce:	nas to be found out by the manufa nentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured Solvent-like	
Penetratio The exact has to be of For the mini- (Permeation Eye prote Body prote Body prote Body prote Body prote Body prote Body prote Ceneral In Appearan Form: Colour: Odour: Odour thr pH-value:	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. fection: Protective wo l and Chemical F on on basic physical of ormation ce:	has to be found out by the manufa mentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured Solvent-like Not determined.	
Penetratic The exact has to be of For the mil (Permeatic Eye prote Body prote Body prote Body prote Body prote Body prote Ceneral In Appearan Form: Colour: Odour: Odour thr pH-value: Change in Melting	on time of glove mat break through time h observed. Exture of chemicals n on according to EN 37 ction: Not required. fection: Protective we dand Chemical F on on basic physical formation ce: eshold:	has to be found out by the manufa mentioned below the penetration 74 Part 3: Level 1). ork clothing Properties I and chemical properties Liquefied gas Gold coloured Solvent-like Not determined. Not determined.	time has to be at least 60 minut

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

	(Contd. of page
· Flash point:	<0 °C
[.] Flammability (solid, gas):	Not applicable.
· Ignition temperature:	310 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation o explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	8.5 Vol %
· Vapour pressure at 20 °C:	2,100 hPa
· Density at 20 °C:	0.628 g/cm³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
[.] Other information	No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

Г

· LD/LC50 values relevant for classification:				
106-97-8	butane			
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)		
		800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		

LC50 / 4h 658 mg/l (rat)

NOAEC 4,000-16,000 ppm (rat)

NOAEC 7.2-21.4 mg/l (rat)

(Contd. on page 6)

AU

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

		(Contd. of page 5)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocar	bons, C7-C9, n	n-alkanes, isoalkanes, cyclics
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
	LD50	2,800-3,100 mg/kg (rat)
Inhalative	LC50 / 4h	23.3 mg/l (rat)
	NOAEC	5.8-24.3 mg/l (rat)
74-98-6 pi	ropane	
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.214-21.394 mg/l (rat)
	LOAEC	21.64 mg/l (rat)
	LOAEC	12,000 ppm (rat)
75-28-5 is	obutane	
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.214-21.394 mg/l (rat)
	LOAEC	21.641 mg/l (rat)
	LOAEC	12,000 ppm (rat)
· Primary i	ritant effect:	1

Primary irritant effect:

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

• Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological Information

· Toxicity

· Aquatio	c toxicity:
106-97-	8 butane
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
Hydroc	arbons, C7-C9, n-alkanes, isoalkanes, cyclics
EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
	(Contd. on page 7)

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

	(Contd. of pa
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)
EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/l/72h (aquatic invertebrates)
74-98-6	propane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
	isobutane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
	ence and degradability No further relevant information available. Sour in environmental systems:
· Bioaccu	imulative potential
106-97-8	8 butane
Partition	coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)
Hydroca	arbons, C7-C9, n-alkanes, isoalkanes, cyclics
Biodegra	adability 98 % (28d) (Biodegradability) (OECD 301 F)
74-98-6	propane
Partition	coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)
75-28-5	isobutane
Partition	coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)
Biodegra	adability 100 % (28d) (Biodegradability)
• Addition • General Water ha Do not a sewage	azard class 1 (according to Appendix 1 AwSV): slightly hazardous for water allow undiluted product or large quantities of it to reach ground water, water cours system.
• PBT: No • vPvB: N	of PBT and vPvB assessment ot applicable. lot applicable. dverse effects No further relevant information available.
June a	

(Contd. on page 8)

AU

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

UN-Number	
ADG, IMDG, IATA	UN1950
UN proper shipping name	
ADG	1950 AEROSOLS
IMDG	AEROSOLS
ΙΑΤΑ	AEROSOLS, flammable
Transport hazard class(es)	
ADG	
	2.55 00000
Class	2 5F Gases. 2.1
Label IMDG, IATA	۷. ۱
Class Label	2.1 2.1
Packing group	- .,
ADG, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity o litre: Category A. For AEROSOLS with a capac
	above 1 litre: Category B. For WASTE AEROSOL
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity o
	litre: Segregation as for class 9. Stow "separat
	from" class 1 except for division 1.4. For AEROSO
	with a capacity above 1 litre: Segregation as for t
	appropriate subdivision of class 2. For WAS
	AEROSOLS: Segregation as for the appropriate

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

	(Contd. of page		
	subdivision of class 2.		
Transport in bulk according to Annex II of			
Marpol and the IBC Code	Not applicable.		
Transport/Additional information:			
ADG			
Limited quantities (LQ)	1L		
Excepted quantities (EQ)	Code: E0		
	Not permitted as Excepted Quantity		
Transport category	2		
Tunnel restriction code	D		
IMDG			
Limited quantities (LQ)	1L		
Excepted quantities (EQ)	Code: E0		
	Not permitted as Excepted Quantity		
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1		

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

106-97-8	butane	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
74-98-6	propane	
75-28-5	isobutane	
78-78-4	isopentane	
7440-50-8	copper	
Standard i	for the Uniform Scheduling of Medicines and Poisons	
None of the	e ingredients is listed.	

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness.

· Department issuing SDS: Abteilung Produktsicherheit

(Contd. on page 10)

[·] AU -

Printing date 04.04.2019

Version number 4.0

Revision: 04.04.2019

Trade name: COPPER SPRAY

(Contd. of page 9)
· Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure – Compressed gas
Fless. Gas C. Gases under pressure – Compressed gas Flam. Lig. 2: Flammable liquids – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
* Data compared to the previous version altered.