

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

#### 1 Identification

- · Product identifier
- · Trade name: RACING FORK OIL 15W
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture

Only for proper handling.

Fork oil

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal

Telefon +41 (0)62 919 75 75

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD

Australia Phone : 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

#### 2 Hazard(s) Identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butyl methacrylate

Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

(Contd. of page 1)

## Safety Data Sheet according to WHS Regulations

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		·
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	≥25-≤50%
CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304	<i>≥</i> 2.5- <i>≤</i> 10%
CAS: 64742-46-7 EINECS: 265-148-2	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	<i>≥</i> 1- <i>≤</i> 7.5%
CAS: 97-88-1 EINECS: 202-615-1 Index number: 607-033-00-5	n-butyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-≤0.25%

#### · Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

Advice for firefighters

· Protective equipment: No special measures required.

(Contd. of page 2)

#### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class: 10
- · **Specific end use(s)** No further relevant information available.

#### 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs		
64742-53-	6 Distillates (petroleum), hydrotreated light nap	hthenic
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)
72623-87-	1 Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)
	DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)
64742-46-	7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes	s, cycloalkanes, <0.03% aromatics
Dermal	DNEL / Workers / Systemic effects / Long-term	2.9 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term	16 mg/m3 (worker)

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

#### Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye protection: Goggles recommended during refilling

· Body protection: Protective work clothing

#### 9 Physical and Chemical Properties

Appearance:	<b></b>
Form:	Fluid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ra	nge: Undetermined.
Flash point:	>200 °C
Flammability (solid, gas):	Not applicable.
lgnition temperature:	>270 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

	(0	Contd. of page 4
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure at 20 °C:	1.6 hPa	
Density at 20 °C:	0.892 g/cm³ (ASTM D 4052)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	71.9 mm²/s @ 40 °C	
Solids content:	0.0 %	
Other information	No further relevant information available.	

## 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

64742-53-	6 Distillate	es (petroleum), hydrotreated light naphthenic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
72623-87-	1 Lubricat	ing oils (petroleum), C20-50, hydrotreated neutral oil-based
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
		(Contd. on pag

AU

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

		(Contd. of page 5)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	_	2.18-5.53 mg/l (rat)
Illilalative	NOAEC	
		980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
		rbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	25-125 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	30 mg/kg/24h (rat)
Inhalative	LC50 / 4h	1.72-4.6 mg/l (rat)
	NOAEC	880-1,710 mg/m3 (rat)
	LOEL	23-24 mg/m3 (rat)
97-88-1 n-	butyl meti	hacrylate
Oral	LD50	22,600 mg/kg (rat)
Dermal	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50 / 4h	4,910 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

### 12 Ecological Information

· Toxicity

64742	2-53-6 Distillates (petroleum), hydrotreated light naphthenic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
LL50	10,000 mg/l/24h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	
72623	3-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
LL50	10,000 mg/l/24h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	

Version number 1.1 Revision: 04.04.2019 Printing date 04.04.2019

Trade name: RACING FORK OIL 15W

64742	(Contd. of page 6) 2-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
	1.13-65 mg/l/96h (fish)
LL50	21-150 mg/l/72h (fish)
LL50	28-180 mg/l/48h (fish)
LL50	100-1,000 mg/l/24h (fish)
EL50	7.385-210 mg/l/48h (aquatic invertebrates)
EL50	180-1,000 mg/l/24h (aquatic invertebrates)
EL50	1.714-22 mg/l/72h (algae / cyanobacteria)

- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:

· Bioaccumulative p	potential
64742-53-6 Distilla	tes (petroleum), hydrotreated light naphthenic
Partition coefficient	2-6 [] (log Kow) (Bioaccumulation)
64742-46-7 Hydrod	carbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Biodegradability	74 % (28d) (Biodegradability) (OECD 306)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Contact waste processors for recycling information.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
· ADG, ADN, IMDG, IATA	Void	
UN proper shipping name		
ADG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
ADG, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADG, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

		(Contd. of page 7)
· Special precautions for user	Not applicable.	
· Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

#### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	Inventory of Chemical Substances	
	Distillates (petroleum), hydrotreated heavy naphthenic	
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
64742-62-7	Residual oils (petroleum), solvent-dewaxed	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
64742-46-7	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
97-88-1	n-butyl methacrylate	
64742-47-8	Distillates (petroleum), hydrotreated light	
33703-08-1	Diisononyladipat	
25307-17-9	2,2'-(9-octadecenylimino)bisethanol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Standard fo	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7		13

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)

Page 9/9

## Safety Data Sheet according to WHS Regulations

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 15W

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

(Contd. of page 8)