

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

1 Identification

- · Product identifier
- · Trade name: RACING FORK OIL 4W
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Only for proper handling.

Fork oil

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal Telefon +41 (0)62 919 75 75

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light naphthenic

Distillates (petroleum), hydrotreated light naphthenic

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics

· Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

(Contd. of page 1)

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	25-50%
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	≥25-≤50%
CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304	≥1-≤7.5%
CAS: 64742-46-7 EINECS: 265-148-2	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	≥0.25-≤2.5%

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

(Contd. on page 3)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

(Contd. of page 2)

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

- · Information about fire and explosion protection: Do not heat above flash point.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store containers closed and protect against rain, dust, heat and other atmospheric influences. Keep container tightly sealed.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

6 Distillates (petroleum), hydrotreated light nap	hthenic
DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)
6 Distillates (petroleum), hydrotreated light nap	hthenic
DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)
1 Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based
DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)
DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)
7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes	s, cycloalkanes, <0.03% aromatics
DNEL / Workers / Systemic effects / Long-term	2.9 mg/kg/24h (worker)
DNEL / Workers / Systemic effects / Long-term	16 mg/m3 (worker)
	DNEL / Workers / Local Effects / Long-term 6 Distillates (petroleum), hydrotreated light nap DNEL / Workers / Local Effects / Long-term 1 Lubricating oils (petroleum), C20-50, hydrotre DNEL / Workers / Local Effects / Long-term DNEL/general population/Local effects/Long-term 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes DNEL / Workers / Systemic effects / Long-term

Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

(Contd. of page 3)

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

General Information	
Appearance:	
Form:	Fluid
Colour:	Red
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	: Undetermined.
Flash point:	120 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>270 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.

(Contd. on page 5)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

	(Contd	. of page 4
· Vapour pressure:	Not determined.	
Density at 20 °C:	0.881 g/cm³ (ASTM D 4052)	
· Relative density	Not determined.	
Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	15.9 mm²/s @ 40 °C	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity

64742-53-	6 Distillate	s (petroleum), hydrotreated light naphthenic	
Oral	LD50	5,000 mg/kg (rat)	
	LOAEL	125 mg/kg/24h (rat)	
Dermal	LD50	2,000-5,000 mg/kg (rabbit)	
	NOEL	30-2,000 mg/kg/24h (rat)	
	NOAEL	150 mg/kg/24h (mouse)	
		1,000 mg/kg/24h (rabbit)	
	LOAEL	100 mg/kg/24h (mouse)	
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)	
	NOEL	220 mg/m3 (rat)	
	NOAEL	980 mg/m3 (rat)	
64742-53-	6 Distillate	s (petroleum), hydrotreated light naphthenic	
Oral	LD50	5,000 mg/kg (rat)	
	LOAEL	125 mg/kg/24h (rat)	
Dermal	LD50	2,000-5,000 mg/kg (rabbit)	
	NOEL	30-2,000 mg/kg/24h (rat)	
	NOAEL	150 mg/kg/24h (mouse)	
		1,000 mg/kg/24h (rabbit)	
	ı		(Contd. on pag

- AL

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

		(Contd. of page 5
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
72623-87-	1 Lubricat	ing oils (petroleum), C20-50, hydrotreated neutral oil-based
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
64742-46-	7 Hydroca	rbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	25-125 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	30 mg/kg/24h (rat)
Inhalative	LC50 / 4h	1.72-4.6 mg/l (rat)
	NOAEC	880-1,710 mg/m3 (rat)
	LOEL	23-24 mg/m3 (rat)

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological Information

· Toxicity

64742	-53-6 Distillates (petroleum), hydrotreated light naphthenic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
LL50	10,000 mg/l/24h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	
64742	-53-6 Distillates (petroleum), hydrotreated light naphthenic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	

- AU

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

	(Contd. of page 6)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
72623	8-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
64742	2-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
LL50	1.13-65 mg/l/96h (fish)
LL50	21-150 mg/l/72h (fish)
LL50	28-180 mg/l/48h (fish)
LL50	100-1,000 mg/l/24h (fish)
EL50	7.385-210 mg/l/48h (aquatic invertebrates)
EL50	180-1,000 mg/l/24h (aquatic invertebrates)
EL50	1.714-22 mg/l/72h (algae / cyanobacteria)
Persi	stence and degradability No further relevant information available.

- Behaviour in environmental systems:

Benaviour in envir	omnentar systems.
· Bioaccumulative p	otential
64742-53-6 Distilla	tes (petroleum), hydrotreated light naphthenic
Partition coefficient	2-6 [] (log Kow) (Bioaccumulation)
64742-53-6 Distilla	tes (petroleum), hydrotreated light naphthenic
Partition coefficient	2-6 [] (log Kow) (Bioaccumulation)
64742-46-7 Hydroc	arbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Biodegradability	74 % (28d) (Biodegradability) (OECD 306)

· Mobility in soil No further relevant information available.

- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Version number 1.1 Revision: 04.04.2019 Printing date 04.04.2019

Trade name: RACING FORK OIL 4W

(Contd. of page 7)

UN-Number		
ADG, ADN, IMDG, IATA	Void	
UN proper shipping name ADG, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
ADG, ADN, IMDG, IATA Class	Void	
Packing group ADG, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
	Distillates (petroleum), hydrotreated light naphthenic	
64742-62-7	Residual oils (petroleum), solvent-dewaxed	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
64742-46-7	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
97-88-1	n-butyl methacrylate	
64742-47-8	Distillates (petroleum), hydrotreated light	
33703-08-1	Diisononyladipat	
25307-17-9	2,2'-(9-octadecenylimino)bisethanol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
Standard fo	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7		3

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

(Contd. on page 9)

Printing date 04.04.2019 Version number 1.1 Revision: 04.04.2019

Trade name: RACING FORK OIL 4W

(Contd. of page 8)

No special training instructions to ensure protection of human health and environment are required.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

· Department issuing SDS: Abteilung Produktsicherheit

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

AU