

Version number 1.0

Revision: 04.04.2019

### 1 Identification

- · Product identifier
- Trade name: <u>RACING SHOCK OIL</u>
- **Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- **Application of the substance / the mixture** Lubricant Only for proper handling.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX–Schmiertechnik Bern–Zürich–Strasse 31 CH–4901 Langenthal Telefon +41 (0)62 919 75 75

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD Australia Phone : 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

### 2 Hazard(s) Identification

· Classification of the substance or mixture

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS). **Hazard pictograms** 



- · Signal word Danger
- · Hazard-determining components of labelling: Distillates (petroleum), hydrotreated light naphthenic Distillates (petroleum), hydrotreated light naphthenic Dec-1-ene, dimers, hydrogenated Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based · Hazard statements H304 May be fatal if swallowed and enters airways. Precautionary statements P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting. P331 P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

AU -

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

### Trade name: RACING SHOCK OIL

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	25-50%
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	<i>≥</i> 25- <i>≤</i> 50%
CAS: 68649-11-6 NLP: 500-228-5	Dec-1-ene, dimers, hydrogenated Asp. Tox. 1, H304; Acute Tox. 4, H332	10-25%
CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304	<i>≥</i> 1- <i>≤</i> 7.5%
CAS: 64742-46-7 EINECS: 265-148-2	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	<i>≥</i> 0.25- <i>≤</i> 2.5%

### · Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental Release Measures

• Personal precautions, protective equipment and emergency procedures Not required.

, (Contd. on page 3)

(Contd. of page 1)

<sup>-</sup> AU

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

Trade name: RACING SHOCK OIL

(Contd. of page 2) · Environmental precautions: Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

· Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

### 7 Handling and Storage

· Handling:

• **Precautions for safe handling** No special precautions are necessary if used correctly.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities

· Storage:

DNFLS

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

· Storage class: 10

· Specific end use(s) No further relevant information available.

### 8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

64742-53-	6 Distillates (petroleum), hydrotreated light naphth	nenic
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)
64742-53-	6 Distillates (petroleum), hydrotreated light naphth	nenic
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)
68649-11-	6 Dec-1-ene, dimers, hydrogenated	
Inhalative	DNEL/Workers/Systemic effects/acute-short term	60 mg/m3 (worker)
	DNEL/general pop/Systemic effects/acute-short term	50 mg/m3 (consumer)
72623-87-	1 Lubricating oils (petroleum), C20-50, hydrotreate	d neutral oil-based
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)
	DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)
64742-46-	7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, c	ycloalkanes, <0.03% aromatics
Dermal	DNEL / Workers / Systemic effects / Long-term	2.9 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term	16 mg/m3 (worker)

allon. The lists valid during the making

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

### Do not inhale gases / fumes / aerosols.

### Respiratory protection:

Not necessary if room is well-ventilated.

(Contd. on page 4)

AU

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

### Trade name: RACING SHOCK OIL

(Contd. of page 3) Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK. • **Protection of hands:** 

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Fluorocarbon rubber (Viton) Nitrile rubber, NBR

- Recommended thickness of the material:  $\geq 0.4 \text{ mm}$
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

### 9 Physical and Chemical Properties

Appearance:	
Form:	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Solidification point:	
Pouring point	<-45 °C
Flash point:	123 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	0.868 g/cm³ (ASTM D 4052)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.

*Printing date 04.04.2019* 

Version number 1.0

Revision: 04.04.2019

(Contd. of page 4)

Trade name: RACING SHOCK OIL

· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	

Dynamic:

Kinematic:

• Other information

Not determined. 14.2 mm²/s @ 40 °C No further relevant information available.

### 10 Stability and Reactivity

· Reactivity No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

### · Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

Oral	LD50	es (petroleum), hydrotreated light naphthenic 5,000 mg/kg (rat)
Ulai		
Dennel	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative		2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
64742-53-	6 Distillate	es (petroleum), hydrotreated light naphthenic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
68649-11-	6 Dec-1-en	ne, dimers, hydrogenated
Oral	LD50	2,000-5,000 mg/kg (rat)
	NOAEL	1,000-6,771 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)

AU

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

Trade name: RACING SHOCK OIL

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
64742-46-	7 Hydroca	rbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	25-125 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	30 mg/kg/24h (rat)
Inhalative	LC50 / 4h	1.72-4.6 mg/l (rat)
	NOAEC	880-1,710 mg/m3 (rat)
	LOEL	23-24 mg/m3 (rat)

• Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

### 12 Ecological Information

•	То	xic	ity
---	----	-----	-----

· Aquat	ic toxicity:	
64742-	-53-6 Distillates (petroleum), hydrotreated light naphthenic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
LL50	10,000 mg/l/24h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	
64742-	-53-6 Distillates (petroleum), hydrotreated light naphthenic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
LL50	10,000 mg/l/24h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	
L	,	(Contd. on page 7)

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

Trade name: RACING SHOCK OIL

NOEC         2 r           NOEC         23           NOEC         1,0           T2623-87-         10           LL50         10           LL50         10           LL50         10           LL50         10           LL50         10           LL50         10           EL50         10           EL50         10           EL50         1.1           LL50         28           LL50         10           EL50         1.2           BEL50         1.3           EL50         1.7           Persistend         Behaviou           Bioaccum         64742-53-           Partition co         64742-53-	6 Dec-1-ene, dimers, hydrogenated         ng//28d (microorganisms)         4-23.5 mg/l/14d (microorganisms)         000 mg/l/3h (microorganisms)         1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based         000 mg/l/96h (aquatic invertebrates)         0 mg/l/96h (fish)         000 mg/l/24h (aquatic invertebrates)         7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic         3-65 mg/l/96h (fish)         -150 mg/l/24h (fish)         -150 mg/l/24h (fish)         -201,000 mg/l/24h (fish)         -210 mg/l/24h (aquatic invertebrates)         -0-1,000 mg/l/24h (aquatic invertebrates)         -0-1,000 mg/l/24h (aquatic invertebrates)         -0-1,000 mg/l/24h (aquatic invertebrates)         -14-22 mg/l/72h (algae / cyanobacteria)         ce and degradability No further relevant information available.         rin environmental systems:         ulative potential         6 Distillates (petroleum), hydrotreated light naphthenic         pefficient [2-6 [] (log Kow) (Bioaccumulation)
NOEC         23           NOEC         1,0           72623-87-         10           LL50         10           EL50         10           EL50         10           EL50         11           LL50         21           LL50         10           EL50         10           EL50         10           EL50         10           EL50         10           Behaviout         10           Bioaccum         64742-53-           Partition co         64742-53-	4-23.5 mg/l/14d (microorganisms) 00 mg/l/3h (microorganisms) <b>1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based</b> 000 mg/l/96h (aquatic invertebrates) 0 mg/l/96h (fish) 000 mg/l/72h (aquatic invertebrates) 000 mg/l/24h (aquatic invertebrates) 000 mg/l/24h (aquatic invertebrates) 000 mg/l/24h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -150 mg/l/24h (fish) 000 mg/l/24h (fish) 000 mg/l/24h (fish) 000 mg/l/24h (fish) 000 mg/l/24h (aquatic invertebrates) 014-22 mg/l/72h (algae / cyanobacteria) Ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
NOEC         1,0           72623-87-         10           LL50         10           EL50         10           EL50         10           EL50         10           EL50         1.1           LL50         28           LL50         18           EL50         1.7           Persistem           Behaviou         10           G4742-53-           Partition co           64742-53-	000 mg/l/3h (microorganisms)         1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based         000 mg/l/96h (aquatic invertebrates)         0 mg/l/96h (fish)         000 mg/l/72h (aquatic invertebrates)         000 mg/l/48h (aquatic invertebrates)         000 mg/l/24h (aquatic invertebrates)         7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic
LL50       10         LL50       10         LL50       10         LL50       10         LL50       10         EL50       10         64742-46-         LL50       21         LL50       21         LL50       21         LL50       10         EL50       10         EL50       10         EL50       10         EL50       13         EL50       1.7         Persisten       Behaviou         Bioaccum       64742-53-         Partition co       648649-11-	0000 mg/l/96h (aquatic invertebrates) 0 mg/l/96h (fish) 000 mg/l/72h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 000 mg/l/24h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -150 mg/l/24h (fish) -150 mg/l/24h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 185-210 mg/l/48h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) Ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
10         LL50       10         LL50       10         EL50       10         EL50       10         64742-46-       11         LL50       21         LL50       21         LL50       28         LL50       10         EL50       10         EL50       10         EL50       10         EL50       13         EL50       1.7         Persistem       Behaviou         Bioaccum       64742-53-         Partition co       648649-11-	0 mg/l/96h (fish) 000 mg/l/72h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -150 mg/l/72h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 285-210 mg/l/48h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) Ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       10         LL50       10         EL50       10         64742-46-       1.1         LL50       21         LL50       21         LL50       28         LL50       10         EL50       10         EL50       1.1         EL50       10         EL50       10         EL50       1.3         EL50       1.7         Persistend       Behaviou         Bioaccum       64742-53-         Partition co       64649-11-	000 mg/l/72h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -150 mg/l/72h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 185-210 mg/l/48h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) Ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       10         LL50       10         EL50       10         64742-46-       10         LL50       21         LL50       21         LL50       28         LL50       10         EL50       10         EL50       10         EL50       13         EL50       1.7         Persisten       Behaviou         Bioaccum       64742-53-         Partition co       64649-11-	000 mg/l/48h (aquatic invertebrates) 000 mg/l/24h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) 150 mg/l/72h (fish) 180 mg/l/24h (fish) 0-1,000 mg/l/24h (fish) 285-210 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       10         EL50       10         64742-46-       1.1         LL50       21         LL50       28         LL50       28         LL50       10         EL50       10         EL50       10         EL50       10         EL50       1.7         Persistem       Behaviou         Bioaccum       64742-53-         Partition co       648649-11-	000 mg/l/24h (aquatic invertebrates) 000 mg/l/48h (aquatic invertebrates) 7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -150 mg/l/24h (fish) -180 mg/l/24h (fish) 0-1,000 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
EL50       10         64742-46-       1.1         LL50       21         LL50       28         LL50       10         EL50       10         EL50       10         EL50       1.3         EL50       1.3         Behaviou       1.7         Bioaccum       64742-53-         Partition co       64742-53-         Partition co       68649-11-	000 mg/l/48h (aquatic invertebrates) <b>7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, &lt;0.03% aromatic</b> 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 285-210 mg/l/48h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) <b>Ce and degradability</b> No further relevant information available. <b>r in environmental systems:</b> <b>ulative potential</b> <b>6 Distillates (petroleum), hydrotreated light naphthenic</b>
64742-46-         LL50       1.1         LL50       21         LL50       28         LL50       10         EL50       10         EL50       1.3         EL50       1.4         Behaviou       1.4         Bioaccum       64742-53-         Partition co       64742-53-         Partition co       68649-11-	7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic 3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -180 mg/l/24h (fish) 0-1,000 mg/l/24h (fish) 285-210 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 214-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       1.1         LL50       21         LL50       28         LL50       10         EL50       7.3         EL50       1.7         Persistem         Behaviou         Bioaccum         64742-53-         Partition co         64742-53-         Partition co         64649-11-	3-65 mg/l/96h (fish) -150 mg/l/72h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 885-210 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       21         LL50       28         LL50       10         EL50       1.3         EL50       1.7         Persisten         Behaviou         Bioaccum         64742-53-         Partition co         64649-11-	-150 mg/l/72h (fish) -180 mg/l/48h (fish) 0-1,000 mg/l/24h (fish) 0-1,000 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) <b>ce and degradability</b> No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
LL50       28         LL50       10         EL50       7.3         EL50       18         EL50       1.7         Persisten         Behaviou         Bioaccum         64742-53-         Partition co         68649-11-	-180 mg/l/48h (fish) D-1,000 mg/l/24h (fish) D-1,000 mg/l/24h (aquatic invertebrates) D-1,000 mg/l/24h (aquatic inverte
LL50       10         EL50       7.3         EL50       18         EL50       1.7         Persisten         Behaviou         Bioaccum         64742-53-         Partition co         64649-11-	0-1,000 mg/l/24h (fish) 185-210 mg/l/24h (aquatic invertebrates) 0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) <b>ce and degradability</b> No further relevant information available. <b>r in environmental systems:</b> <b>ulative potential</b> 6 Distillates (petroleum), hydrotreated light naphthenic
EL50       7.3         EL50       18         EL50       1.7         Persisten       8         Behaviou       8         Bioaccum       64742-53-         Partition       co         64742-53-       7         Partition       co         64649-11-       10	285-210 mg/l/48h (aquatic invertebrates) D-1,000 mg/l/24h (aquatic invertebrates) 214-22 mg/l/72h (algae / cyanobacteria) Ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
EL50       18         EL50       1.7         Persisten       Behaviou         Bioaccum       64742-53-         Partition       co         64742-53-       Partition         Partition       co         64649-11-       68649-11-	0-1,000 mg/l/24h (aquatic invertebrates) 14-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
EL50         1.7           Persisten         Behaviou           Bioaccum         64742-53-           Partition co         64742-53-           Partition co         64742-53-           Partition co         64649-11-	14-22 mg/l/72h (algae / cyanobacteria) ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
Persisten Behaviou Bioaccum 64742-53- Partition co 64742-53- Partition co 68649-11-	ce and degradability No further relevant information available. r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
<b>Behaviou</b> <b>Bioaccum</b> <b>64742-53-</b> Partition co <b>64742-53-</b> Partition co <b>68649-11-</b>	r in environmental systems: ulative potential 6 Distillates (petroleum), hydrotreated light naphthenic
64742-53- Partition co 64742-53- Partition co 68649-11-	6 Distillates (petroleum), hydrotreated light naphthenic
Partition co 64742-53- Partition co 68649-11-	
64742-53- Partition co 68649-11-	
Partition co	
68649-11-	6 Distillates (petroleum), hydrotreated light naphthenic pefficient 2-6 [] (log Kow) (Bioaccumulation)
	6 Dec-1-ene, dimers, hydrogenated
Dartition of	pefficient   6.5 [] (log Kow) (Bioaccumulation)
Biodegrad	
•	7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatic
Biodegrad	
	<b>a soil</b> No further relevant information available.
Additiona General n	l ecological information:
Do not all sewage sy	ow undiluted product or large quantities of it to reach ground water, water cours stem.
PBT: Not a	f <b>PBT and vPvB assessment</b> applicable. applicable.
	erse effects No further relevant information available.

· Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

(Contd. on page 8)

ÂU

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

Trade name: RACING SHOCK OIL

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number	\ / - <sup>1</sup> - 1	
ADG, ADN, IMDG, IATA	Void	
· UN proper shipping name		
ADG, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
ADG, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADG, IMDG, IATA	Void	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

### 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	Inventory of Chemical Substances	
	Distillates (petroleum), hydrotreated light naphthenic	
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
68649-11-6	Dec-1-ene, dimers, hydrogenated	
64742-62-7	Residual oils (petroleum), solvent-dewaxed	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
64742-46-7	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics	
72623-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
97-88-1	n-butyl methacrylate	
64742-47-8	Distillates (petroleum), hydrotreated light	
33703-08-1	Diisononyladipat	
25307-17-9	2,2'-(9-octadecenylimino)bisethanol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
· Standard fo	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7	xvlene	S

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

AU

(Contd. of page 7)

Printing date 04.04.2019

Version number 1.0

Revision: 04.04.2019

### Trade name: RACING SHOCK OIL

(Contd. of page 8)

for any specific product features and sh The classification of the mixture was o down in Annex I of Regulation (EC) No	knowledge. However, this shall not constitute I not establish a legally valid contractual relati rried out by calculation in accordance with 272/2008. protection of human health and environment a	onship. the rules l
• <b>Relevant phrases</b> H304 May be fatal if swallowed and enter H332 Harmful if inhaled.		2.01090110
Department issuing SDS: Abteilung Plating Abbreviations and acronyms: ADR: Accord européen sur le transport des main International Carriage of Dangerous Goods by Ro IMDG: International Maritime Code for Dangerous IATA: International Maritime Code for Dangerous IATA: International Air Transport Association EINECS: European Inventory of Existing Comme ELINCS: European List of Notified Chemical Sub CAS: Chemical Abstracts Service (division of the DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Asp. Tox. 1: Aspiration hazard – Category 1 * Data compared to the previous verse	nandises dangereuses par Route (European Agreemen d) Goods ial Chemical Substances ances merican Chemical Society)	t concerning