

MUC-OFF DRIVETRAIN CLEANER

Page: 1

Compilation date: 24/05/2021

Revision date: 01/01/2022

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: MUC-OFF DRIVETRAIN CLEANER

Product code: 295-CT,295-S,295FR,295JP,295ES,295DE,295ES,295CEE,304,304DE,304-S,255

807,808,319-CT,319-S

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Muc-Off Ltd

UK - Muc-Off Ltd, Unit 23 Branksome Business Park, Bourne Valley Road, Poole, Dorset, BH12 1DW

EU- Muc-Off Ltd, Unit 3D North Point House, North Point Business Park, New Mallow Road, Cork,

Ireland, T23 AT2P

Tel: +44(0)1202 307790 Email: info@muc-off.com

1.4. Emergency telephone number

Emergency tel: +44 (0)1202 307790

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most important adverse effects: May be fatal if swallowed and enters airways. Causes skin irritation.

Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





MUC-OFF DRIVETRAIN CLEANER

Page: 2

Signal words: Danger

Precautionary statements: P280: Wear protective gloves/eye protection.

P301+310: IF SWALLOWED: Immediately call a first aid. P302+352: IF ON SKIN: Wash with plenty of water/soap.

P331: Do NOT induce vomiting.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance. UFI CODE :QJY1-S0KD-Y00C-P7XA

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304; -: EUH066	>70%

BUTYL GLYCOL - REACH registered number(s): 01-2119475108-36

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox.	10-
			4: H312; Acute Tox. 4: H302;	30%
			Eye Irrit. 2: H319; Skin Irrit. 2:	
			H315	

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL) - REACH registered number(s): 01-2119490100-53

931-329-6	68155-07	-	Aquatic Chronic 2: H411; Eye	1-5%
	-7		Dam. 1: H318; Skin Irrit. 2: H315	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to

skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

MUC-OFF DRIVETRAIN CLEANER

Page: 3

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

MUC-OFF DRIVETRAIN CLEANER

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTYL GLYCOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of

emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Yellow

Odour: Sweet-smelling

Evaporation rate: Slow

Oxidising: Not applicable.

Solubility in water: Miscible

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: <20.5

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3219)

Boiling point/range°C: >35 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point °C: 60 - 93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: Not applicable. [cont...]

MUC-OFF DRIVETRAIN CLEANER

Page: 5

Vapour pressure: No data available.

Relative density: 0.835 pH: Not applicable.

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage

conditions. Decomposition may occur on exposure to conditions or materials

listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

BUTYL GLYCOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	1746	mg/kg

MUC-OFF DRIVETRAIN CLEANER

Page: 6

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL)

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Daphnia magna	48H EC50	>10	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>10	mg/l

BUTYL GLYCOL

ALGAE	72H ErC50	1840	mg/l
DAPHNIA	48H EC50	1550	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1474	mg/l

AMIDES, C8-18 (EVEN NUMBERED) AND C18-UNSATD, N,N-BIS(HYDROXYETHYL)

ALGAE	72H IC50	3.9	mg/l
DAPHNIA	72H ErC50	3.2	mg/l
FISH	96H LC50	2.4	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

MUC-OFF DRIVETRAIN CLEANER

Page: 7

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised

disposal company.

NB: The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixt

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission

Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be

all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the

above product.