

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: Silencer Brake Service Spray

· Article number: 9130

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture: Coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer

· IGRALUB AG für Schmiertechnik Rex Articoli Tecnici SA · Mainaustrasse 15 Via Catenazzi 1

· CH-8008 Zürich / Switzerland CH-6850 Mendrisio / Switzerland

· info@igralub.ch sales@rex.ch

· Further information obtainable from: Product safety department

• 1.4 Emergency telephone number: During normal opening times: +41 44 251 51 51

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

H315 Skin Irrit. 2 Causes skin irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

(Contd. of page 1)

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1, H220	30-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220	10-20%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315; STOT SE 3, H336	10-20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas C, H280	10-20%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33	Hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclic Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	1-10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Page 3/8

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

(Contd. of page 2)

 $\cdot \textit{ 4.3 Indication of any immediate medical attention and special treatment needed} \\$

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed

· Eye protection: Not required.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol
Colour: Dark grey
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: -60 °C

Flammability (solid, gas): Not applicable.

(Contd. on page 5)

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

	(Contd. of pag
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.9 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C:	4,000 hPa
Density at 20 °C:	0.64g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	80.4 %
VOC (EC)	80.41 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
Hydrocarbons, C6, isoalkanes, <5% n-hexane			
Oral	LD50	>5,000 mg/kg (rat) (OECD- Prüfrichtlinie 401)	
Dermal	LC50	>3,000 mg/kg (rat) (OECD- Prüfrichtlinie 402))	
Inhalative	LC50/4 h	>20 mg/l (rat) (OECD- Prüfrichtlinie 403)	
Hydrocard	bons, C7-C	9, n-alkanes, iso-alkanes, cyclic	
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
	•	(Contd. on page 6)	

EU

Page 6/8

(Contd. of page 5)

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C6, isoalkanes, <5% n-hexane

LC50/48h | 3.87 mg/l (Daphnia magna (Großer Wasserfloh))

>1 mg/l (Roter Killifisch (Oryzias latipes))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European		waste			
			-		

15 01 10* packaging containing residues of or contaminated by hazardous substances

15 01 04 metallic packaging

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950

(Contd. on page 7)

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

1.0.101	(Contd. of pag
14.2 UN proper shipping name ADR	1950 AEROSOLS
IMDG	AEROSOLS AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	TIDICOSO ES, frantima esc
ADR	
Class	2 5F Gases.
Lahel	2.1 Guses.
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 lit Category A. For AEROSOLS with a capacity above 1 lit Category B. For WASTE AEROSOLS: Category C, Cla of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 lit Segregation as for class 9. Stow "separated from" clas except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity 2
Transport category Tunnel restriction code	D D
	v
IMDG Limited quantities (LQ)	<i>IL</i>
Excepted quantities (EQ)	TL Code: E0
2copica quantumes (12)	Not permitted as Excepted Quantity
	(Contd. on page

Printing date 30.10.2019 Version number 4 Revision: 30.10.2019

Trade name: Silencer Brake Service Spray

(Contd. of page 7)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.